

# Samoiedo ICE-CREAM SGL 700 S/S



15° -25°C



40%

TENSION  
230V - 50HZ

DEFROST



COOLING



LED LIGHTING



2x1200 lm



## Technical Information

| LAYOUT  |  |  | SHELVES L X P (MM) - NR | VOLUME | GROSS  | NET    | COMPRESSOR   |
|---|---|---|-------------------------|--------|--------|--------|--------------|
|  | L 1180<br>P 620<br>H 1860   | L 1220<br>P 650<br>H 2030   | 460x440 -12             | Lt 742 | Kg 295 | Kg 270 | Watt 700+700 |

## Optionals

- Key closing
- Wire shelf n.1
- Glass shelf n.1
- Shelf for glass and grids (n.4)
- Suction cup (n.4)
- Kit of glass shelves for static system
- Kit adjustable feet
- Looking-glass (n. 1) (except for 520 model)
- Glass with altitude valves (for installations above 800 m)
- "No-fog" door or rear glass for negative display case (except for 250 model)
- Power supply 220 V 60 HZ - power supply 115 V 60 HZ
- Water condensing system for each refrigerating group
- System developed for negative, static display cases (n.1) (except for 250, 350, 520 and 700 models)
- Remote motor unit (n. 1) (up to 10 mt.)
- Hot gas defrosting for each refrigerating group (Only single units)
- 3rd led for static negative display cases (1200 Lumen) (except for 520 models)
- Wooden crate packing