

# Samoiedo CONFECTIONERY SPS 700 R



+4° +10°C



75%

TENSION  
230V - 50HZ

DEFROST



COOLING



LED LIGHTING



2x1200 lm



## Technical Information

LAYOUT			SHELVES L X P (MM) - NR	VOLUME	GROSS	NET	COMPRESSOR
	L 1180 P 620 H 1860	L 1220 P 650 H 2030	ø 452 - 12	Lt 742	Kg 272	Kg 247	Watt 790

## Optionals

- Key dosing
- Wire shelf n.1
- Glass shelf n.1
- Shelf for glass and grids (n.4)
- Suction cup (n.4)
- Kit of glass shelves for static system
- Kit adjustable feet
- Looking-glass (n. 1) (except for 520 model)
- Glass with altitude valves (for installations above 800 m)
- "No-fog" door or rear glass for negative display case (except for 250 model)
- Power supply 220 V 60 HZ - power supply 115 V 60 HZ
- Water condensing system for each refrigerating group
- System developed for negative, static display cases (n.1) (except for 250, 350, 520 and 700 models)
- Remote motor unit (n. 1) (up to 10 mt.)
- Hot gas defrosting for each refrigerating group (Only single units)
- 3rd led for static negative display cases (1200 Lumen) (except for 520 models)
- Wooden crate packing